
Clinic Wipeable 24 × 48 in · 2 in

AP-CL2448-2SV · Clinic collection



Front view, to scale. Depth 2 in (5.1 cm).

NRC	**0.90**
SIZE	**24 × 48 in**
THICKNESS	**2 in**
FACE AREA	**8.0 ft²**
FABRIC	**Wipeable perforated vinyl**
COLOR	**Clinic White**
MOUNTING	**Wall, Z-clips**
PRICE	**$120 CAD each**

A wipeable panel for spaces that are cleaned with disinfectant every day. Edges are eased so there are no sharp corners to chip. Best for: Hospitals, clinics, labs, food service.

Construction

Part	Specification
Core	Rigid mineral wool, 6 lb/ft3 (96 kg/m3), 2 in thick
Frame	Kiln-dried wood perimeter frame; edges hardened with resin
Face	Wipeable perforated vinyl, acoustically transparent, stretched and wrapped to the back. A micro-perforated vinyl face you can wipe down with disinfectant. Absorbs less at high frequencies than open fabrics.
Surface	Flat
Edge	Square edge
Mounting	Wall, Z-clips, hardware included
Approx. weight	10.4 lb
Tolerance	± 1/8 in on width and height

Sound absorption

Tested to ASTM C423, Type A mounting (directly on the wall). Suspended clouds and baffles with an air gap absorb more at low frequencies.

125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	NRC
0.14	0.76	1.04	0.97	0.92	0.89	0.90

Fire and environment

- Surface burning: Class A per ASTM E84 (flame spread 25 or less, smoke developed 450 or less) for the core and standard fabrics. Ask for the fabric test report for Wipeable perforated vinyl.
- Mineral wool core is non-combustible and contains recycled content.
- Face can be wiped with diluted hospital-grade disinfectant.

Installation

Mounts flat to the wall on two interlocking Z-clips. Screw the wall clip into studs or rated anchors, level it, and lift the panel onto it.

Full instructions: installation guide (PDF) at www.acousticpanels.ca/pdf/installation.php