
Grid Tile Wipeable 24 × 48 in · 2 in

AP-TL2448-2SV · Grid Tile collection



Front view, to scale. Depth 2 in (5.1 cm).

NRC	**0.90**
SIZE	**24 × 48 in**
THICKNESS	**2 in**
FACE AREA	**8.0 ft²**
FABRIC	**Wipeable perforated vinyl**
COLOR	**Clinic White**
MOUNTING	**Lay-in ceiling grid tile**
PRICE	**$114 CAD each**

A custom fabric-wrapped tile that drops into a standard 15/16 in T-bar ceiling grid in place of a mineral fiber tile. Best for: Offices, schools, healthcare.

Construction

Part	Specification
Core	Rigid mineral wool, 6 lb/ft3 (96 kg/m3), 2 in thick
Frame	Kiln-dried wood perimeter frame; edges hardened with resin
Face	Wipeable perforated vinyl, acoustically transparent, stretched and wrapped to the back. A micro-perforated vinyl face you can wipe down with disinfectant. Absorbs less at high frequencies than open fabrics.
Surface	Flat
Edge	Square edge
Mounting	Lay-in ceiling grid tile, hardware included
Approx. weight	10.4 lb
Tolerance	± 1/8 in on width and height

Sound absorption

Tested to ASTM C423, Type A mounting (directly on the wall). Suspended clouds and baffles with an air gap absorb more at low frequencies.

125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	NRC
0.14	0.76	1.04	0.97	0.92	0.89	0.90

Fire and environment

- Surface burning: Class A per ASTM E84 (flame spread 25 or less, smoke developed 450 or less) for the core and standard fabrics. Ask for the fabric test report for Wipeable perforated vinyl.
- Mineral wool core is non-combustible and contains recycled content.
- Face can be wiped with diluted hospital-grade disinfectant.

Installation

Lays into a standard 15/16 in T-bar ceiling grid like a regular ceiling tile. Check that the grid is rated for the added weight.

Full instructions: installation guide (PDF) at www.acousticpanels.ca/pdf/installation.php